

Datasheet for #sb1119 DN

Recommendations:

Please read the starter kit user manual (at least installation chapter 5), if available, and have a look at the FAQ at <http://www.alpeslasers.ch/alfaq.pdf>

WARNING: Operating the laser with longer pulses, shorter period, or higher voltage or current than specified in this document may cause damage and will result in loss of warranty, unless agreed upon with Alpes Lasers!

WARNING: Beware of the polarity of the laser. This laser has to be powered with negative bias on the laser contact (= bonding pad, corresponding to the label "laser" on the LLH) and the positive bias on the base contact (= submount, corresponding to the label "base" on the LLH).



Figure 1: Support mounting for #sb1119 DN (please note that the laser is connected to the DN pad drawn in blue)




Figure 2: Output power as a function of the singlemode emission frequencies and temperatures




Figure 3: DC voltage fed to LDD (U_{ldd}) as a function of the singlemode emission frequencies and temperatures

λ [nm]	ν [cm ⁻¹]	P[mW]	Temp[°C]	U_{LDD} [V]	I_{pulse} [A]
4861.6	2056.9	0.1	-30	6.5	0.12
4867.1	2054.6	0.1	-15	6.5	0.14
4867.3	2054.5	0.1	-15	7.5	0.26
4867.8	2054.3	0.2	-15	8.5	0.41
4872.6	2052.3	0.1	0	6.5	0.15
4872.8	2052.2	0.1	0	7.5	0.28
4873.3	2052	0.2	0	8.5	0.42
4873.9	2051.8	0.7	0	9.5	0.61
4877.7	2050.1	0.1	15	6.5	0.17
4877.9	2050.1	0.1	15	7.5	0.29
4878.4	2049.9	0.1	15	8.5	0.44
4879	2049.6	0.5	15	9.5	0.62
4882.9	2048	0.1	30	7	0.24
4883.4	2047.8	0.1	30	8.5	0.46
4884.1	2047.5	0.4	30	9.5	0.63

Table 1 : singlemode optical output power as function of operating parameters




Figure 4: peak voltage and average power vs peak current at 2% dc (the solid squares indicate the maximum singlemode emitted power)




Figure 5: peak voltage and average power vs peak current at 2% dc (including the multimode region)

Note: data taken with 50ns pulses on the laser, 2.5 μ s period.




Figure 6: peak current and average power vs LDD voltage at 2% dc (the solid squares indicate the maximum singlemode emitted power)





Figure 7: peak current and average power vs LDD voltage at 2% dc (including the multimode region)

Figure 6: spectra at different temperatures for various DC currents






Figure 8: spectra at -30C for various LDD voltages (monomode only at threshold)




Figure 9: monomode spectrum at -30C and 6.5V




Figure 10: spectra at -15C for various LDD voltages (monomode up to 8.5V)




Figure 11: spectra at -15C for various LDD voltages (monomode range)

Figure 11: spectra from 0C to 30C for various DC currents

