

Datasheet for #sb120

Recommendations:

Please read the starter kit user manual (at least installation chapter 5), if available, and have a look at the FAQ at <http://www.alpeslasers.ch/alfaq.pdf>

WARNING: Operating the laser with longer pulses, shorter period, or higher voltage or current than specified in this document may cause damage and will result in loss of warranty, unless agreed upon with Alpes Lasers!

WARNING: Beware of the polarity of the laser. This laser has to be powered with negative bias on the laser contact (= bonding pad, corresponding to the label "laser" on the LLH) and the positive bias on the base contact (= submount, corresponding to the label "base" on the LLH).




Figure 1: Support mounting for #sb120 (please note that the laser is connected to the DN pad drawn in blue)




Figure 2: Output power as a function of the singlemode emission frequencies and temperatures




Figure 3: DC voltage fed to LDD (U_{ldd}) as a function of the singlemode emission frequencies and temperatures

λ [nm]	ν [cm ⁻¹]	P[mW]	Temp[°C]	U_{LDD} [V]	I_{pulse} [A]
6008	1664.5	1	-30	14.5	4.22
6014	1662.8	0.8	-15	14.5	4.23
6020.4	1661	0.5	0	14.5	4.24
6027.5	1659.1	0.6	15	15	4.46
6028.9	1658.7	1.3	15	16.5	5.07
6030.3	1658.3	2.4	15	18	5.67
6034.2	1657.2	0.2	30	15	4.44
6035.3	1656.9	0.7	30	16.5	5.04
6036.5	1656.6	1.2	30	18	5.62

Table 1 : singlemode optical output power as function of operating parameters




Figure 4: peak voltage and avg power vs peak current (the solid squares indicate the maximum singlemode emitted power)




Figure 5: peak voltage and avg power vs peak current (including the multimode region)

Note: data taken with 50ns pulses, 2.5 μ s period.




Figure 6: peak current and avg power vs LDD voltage (the solid squares indicate the maximum singlemode emitted power)




Figure 7: peak current and avg power vs LDD voltage (including the multimode region)




Figure 8: spectra at -30C, -15C, 0C, 15C, and 30C for various LDD voltages




Figure 9: spectra at -30C for various LDD voltages (monomode only up to 14.5V)




Figure 10: spectra at -15C for various LDD voltages (monomode only up to 15V)




Figure 11: spectra at 0C for various LDD voltages (monomode only up to 16.5V)




Figure 12: spectra at 15C for various LDD voltages (monomode)




Figure 13: spectra at 30C for various LDD voltages (monomode)