

Datasheet for #sbcw11986 DN

Recommendations:

Please read the User Manual and have a look at the FAQ at <http://www.alpeslasers.ch/?a=142>

WARNING: Operating the laser with higher current or voltage than specified in this document may cause damage and will result in loss of warranty, unless Alpes Lasers has permitted to do so!

WARNING: Beware of the polarity of the laser. This laser has to be powered with negative bias and positive bias on the specific zones drawn below. To use with an ILX Lightwave LDX-3232 laser driver, or equivalent.



Figure 1: Mechanical and electrical interface for #sbcw11986 DN (please note that AlN submount numbering is A08JV)




Figure 2: Output power as a function of the singlemode emission frequencies and temperatures




Figure 3: Applied DC current as a function of singlemode emission frequencies and temperatures

λ [nm]	ν [cm ⁻¹]	P[mW]	Temp[°C]	U_{LASER} [V]	I[A]
6271.6	1594.5	0.2	5	10.1	0.18
6273	1594.1	2.1	5	10.3	0.19
6275.4	1593.5	4.9	5	10.5	0.21
6278	1592.9	7.2	5	10.8	0.23
6280.7	1592.2	9.1	5	11	0.25
6275	1593.6	0.4	10	10.1	0.19
6278	1592.9	3.6	10	10.4	0.21
6280.6	1592.2	5.9	10	10.6	0.23
6283.3	1591.5	7.5	10	10.9	0.25
6283.8	1591.4	7.9	10	11	0.26
6282.5	1591.7	0.3	20	10.2	0.21
6283.7	1591.4	1.4	20	10.3	0.22
6285.5	1591	2.7	20	10.5	0.23
6288.1	1590.3	4.1	20	10.7	0.25
6289.1	1590.1	4.5	20	10.8	0.26
6290.2	1589.8	0.3	30	10.2	0.23
6293.7	1588.9	1.9	30	10.5	0.25
6296.7	1588.1	2.7	30	10.8	0.28
6294.7	1588.6	0.1	35	10.3	0.24
6296.4	1588.2	0.7	35	10.5	0.25
6299.4	1587.4	1.5	35	10.7	0.28
6298.4	1587.7	0.2	40	10.4	0.25
6299.3	1587.5	0.2	40	10.4	0.26
6302.2	1586.7	1	40	10.6	0.28
6304.5	1586.2	0.2	45	10.5	0.27

Table 1: Singlemode optical output power as function of operating parameters.




Figure 4: voltage and avg power vs current in continuous-wave operation (the solid squares indicate the maximum singlemode emitted power)

Note: at 5C: $I_{th}=0.17A$ / $V_{th}=10.1V$ (2-wires measurements). Maximum operation current: 0.26A between 5C and 20C, 0.275A between 30C and 45C.

Figure 3: spectra at different temperatures for various DC currents

